



TECHNICAL DATA SHEET: FLOLUX SHATTAF SERIES

- **Item Name: ABS Shattaf full set**
- **Brand: Flolux**
- **Model: Apex-4401**
- **Dual flow mode**



Technical Details				
				
120CM SS 304 chrome slim double lock shower hose with EPDM inner tube 304 S.S. wires(with red & blue lines) knitted reinforced	304 S.S. chrome long sleeve 35mm	ABS SHATTAF HEAD with brass spintle inside	ABS SHATTAF HEAD with brass Pin inside	1/2" brass chrome conical nut 1/2" brass hex nut, both brass insert

PRODUCT OVERVIEW

The Flolux Shattaf Series features premium, high-durability hygiene spray systems specifically designed to meet rigorous property maintenance standards. Engineered to eliminate common field failures like leakages, rusting, and trigger wear, these sets combine high-grade polymers with robust brass and stainless-steel internal components.

COMPONENT SPECIFICATIONS

1. Flexible Shower Hose

- Length: 120 CM
- Outer Shell: SS 304 Stainless Steel, chrome finished, slim double-lock construction
- Inner Tube: High-grade EPDM rubber core
- Reinforcement: Layered SS 304 stainless steel knitted wire mesh featuring color-coded indicator lines (Red & Blue) for high-pressure durability



2. Connection Ends & Fittings

- Sleeve Dimensions: 35 mm extra-long sleeve for maximum stress-strain protection at connection joints
- Sleeve Material: SS 304 Stainless Steel with a high-polished chrome finish
- Coupling Nut 1: 1/2" Brass chrome-plated conical nut with solid brass insert
- Coupling Nut 2: 1/2" Brass hexagonal nut with solid brass insert

3. Shattaf Spray Head

- Body Material: High-grade, impact-resistant ABS polymer with a polished chrome exterior
- Internal Valve Core: Solid Brass Spindle mechanism ensuring continuous smooth spring action
- Locking Clip: Heavy-duty internal brass pin/clip mechanism preventing trigger misalignment or snapping

PERFORMANCE & COMPLIANCE RATINGS

- Maximum Pressure Capacity: Tested up to 50 Bars (burst pressure resistant)
- Anti-Burst Tech: Knitted wire reinforcement prevents inner tube rupture under continuous static pressure.
- Anti-Rust Architecture: Zero corrosive external elements; utilizing premium SS 304 and solid brass internals.
- Leak Prevention: Double-lock casing paired with dual solid brass inserts ensures a watertight seal.

=====

DISTRIBUTOR CONTACT (UAE) :

VIBCO BUILDING MATERIALS TRADING LLC

Address: S-01, Midfa Building, Al Qusais Ind Area 4, Dubai, UAE

Phone: 04-3280060, 0556622983

Email: info@floluxitalia.com

Website: www.floluxitalia.com
