



TECHNICAL DATA SHEET: FLOLUX SHATTAF SERIES

- **Item Name:** ABS Shattaf full set
- **Brand:** Flolux
- **Model:** Neo-2201



Technical Details				
				
Multi Layer Metal Wired EPDM Inner Tube	35mm SS Long Sleeve	Brass Spindle	Brass clip	Brass Conical Nut
120CM SS 304 chrome slim double lock shower hose with EPDM inner tube 304 S.S. wires(with red & blue lines) knitted reinforced	304 S.S. chrome long sleeve 35mm	ABS SHATTAF HEAD with brass spintle inside	ABS SHATTAF HEAD with brass Pin inside	1/2" brass chrome conical nut 1/2" brass hex nut, both brass insert

PRODUCT OVERVIEW

The Flolux Shattaf Series features premium, high-durability hygiene spray systems specifically designed to meet rigorous property maintenance standards. Engineered to eliminate common field failures like leakages, rusting, and trigger wear, these sets combine high-grade polymers with robust brass and stainless-steel internal components.

COMPONENT SPECIFICATIONS

1. Flexible Shower Hose

- Length: 120 CM
- Outer Shell: SS 304 Stainless Steel, chrome finished, slim double-lock construction
- Inner Tube: High-grade EPDM rubber core
- Reinforcement: Layered SS 304 stainless steel knitted wire mesh featuring color-coded indicator lines (Red & Blue) for high-pressure durability



2. Connection Ends & Fittings

- Sleeve Dimensions: 35 mm extra-long sleeve for maximum stress-strain protection at connection joints
- Sleeve Material: SS 304 Stainless Steel with a high-polished chrome finish
- Coupling Nut 1: 1/2" Brass chrome-plated conical nut with solid brass insert
- Coupling Nut 2: 1/2" Brass hexagonal nut with solid brass insert

3. Shattaf Spray Head

- Body Material: High-grade, impact-resistant ABS polymer with a polished chrome exterior
- Internal Valve Core: Solid Brass Spindle mechanism ensuring continuous smooth spring action
- Locking Clip: Heavy-duty internal brass pin/clip mechanism preventing trigger misalignment or snapping

PERFORMANCE & COMPLIANCE RATINGS

- Maximum Pressure Capacity: Tested up to 50 Bars (burst pressure resistant)
- Anti-Burst Tech: Knitted wire reinforcement prevents inner tube rupture under continuous static pressure.
- Anti-Rust Architecture: Zero corrosive external elements; utilizing premium SS 304 and solid brass internals.
- Leak Prevention: Double-lock casing paired with dual solid brass inserts ensures a watertight seal.

=====

DISTRIBUTOR CONTACT (UAE) :

VIBCO BUILDING MATERIALS TRADING LLC

Address: S-01, Midfa Building, Al Qusais Ind Area 4, Dubai, UAE

Phone: 04-3280060, 0556622983

Email: info@floluxitalia.com

Website: www.floluxitalia.com
